

OEM GNSS Receivers and Enclosures

CLICK THE PRODUCT FOR MORE INFORMATION



	BD910	BD940	BD940-INS	BX940	BD970	BD982	BX982	BD990	BD992	BD992-INS	BX992	MB-Two	ABX-Two
Technology	Maxwell 6	Maxwell 7	Maxwell 7	Maxwell 7	Maxwell 6	Maxwell 6	Maxwell 6	Maxwell 7	Maxwell 7	Maxwell 7	Maxwell 7	Z-Blade	Z-Blade
Size (mm) Weight (g)	41 x 41 x 7 19	51 x 41 x 7 27	67 x 60 x 15 60	149 x 93 x 43 660	100 x 60 x 11.6 62	100 x 84.9 x 11.5 92	261 x 140 x 55 1600	100 x 60 x 11.6 54	100 x 60 x 11.6 60	100 x 60 x 11.6 62	185 x 93 x 43 760	71 x 46 x 11 24	190 x 58 x 160 1270
Channels	220	336	336	336	220	2 x 220	2 x 220	1 x 336	2 x 336	2 x 336	2 x 336	240	2 x 240
Max. Update Rate (Hz)	20	50	100	100	50	50	50	50	50	100	100	50	50
GPS	L1	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2	L1, L2
GLONASS	L1	L1, L2, L3	L1, L2, L3	L1, L2, L3	L1, L2	L1, L2, L3	L1, L2, L3	L1, L2, L3	L1, L2, L3	L1, L2, L3	L1, L2, L3	L1, L2	L1, L2
BeiDou	B1	B1, B2	B1, B2	B1, B2	B1, B2	B1, B2	B1, B2	B1, B2, B3	B1, B2, B3	B1, B2, B3	B1, B2, B3	B1, B2	B1, B2
Galileo	E1	E1, E5a, E5b	E1, E5a, E5b	E1, E5a, E5b	E1, E5a, E5b	E1, E5a, E5b	E1, E5a, E5b	E1, E5a, E5b, E6	E1, E5a, E5b, E6	E1, E5a, E5b, E6	E1, E5a, E5b, E6	E1, E5b	E1, E5b
QZSS	L1	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2, L5	L1, L2	L1, L2
IRNSS	-	L5	L5	L5	-	-	-	L5	L5	L5	L5	-	-
SBAS	L1	L1, L5	L1, L5	L1, L5	L1, L5	L1, L5	L1, L5	L1, L5	L1, L5	L1, L5	L1, L5	L1	L1
L-Band / MSS	-	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓	✓
Trimble RTX™	-	IP / L	IP / L	IP / L	IP	IP / L	IP / L	IP / L	IP / L	IP / L	IP / L	IP / L	IP / L
OmniSTAR®	-	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	-	-
RTK	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
INS Attitude/ Positioning	-	-	✓	✓	-	-	-	-	-	✓	✓	-	-
GNSS Heading/ GNSS Attitude	- / -	- / -	- / -	- / -	- / -	✓ / -	✓ / -	- / -	✓ / -	✓ / -	✓ / -	✓ / -	✓ / ✓
Connector	80-pin	80-pin	44-pin	DE9 & DA26	24-pin + 6-pin	40-pin	DE9 & DA26	44-pin	44-pin	44-pin	DE9 & DA26	28-pin	Various